ROYAL OIL CO.

SPECIALTY LUBRICANTS

ATF MULTI-TRANS

Premium Full Synthetic Automatic Trans Fluid

Premium Synthetic Base Oils

Superior Protection

Provides Superior Shift Quality

Extremely Versatile

Resists Oxidation



"Meeting countless industry specifications for automatic transmission fluids, ATF MULTI-TRANS is as versatile as it is effective. Superior base oils and additives shine in heavily worked transmission applications."



ATF MULTI-TRANS is an outstanding trans fluid that has a premium synthetic base oil. It was designed to be compatible with petroleum oils and many other popular synthetic oils. Due to its quality additive package, users can extend the service life with ATF Multi-Trans.

ATF MULTI-TRANS is suitable for cold temperatures offering a low pour point of -60°F, while also being suitable for high temperatures with a flash point of 367°F. ATF MULTI-TRANS is compatible with most transmissions however do not attempt to use this fluid in continuously variable transmissions (CVT's) or dual clutch transmissions (DCT's). Please look to the back for specifications and transmissions ATF-MULTI-TRANS meets or exceeds.

ATF MULTI-TRANS

Product Specifications

Filtered Down to 10 Microns

Foam-Tendency/Stability

Sequence I, ml. 5/0 Sequence II, ml. 5/0 Sequence III, ml. 5/0

Viscosity Index 193

Viscosity cSt at 100 °C 7.3 Flash Point, °F, C.O.C 367

Pour Point, °F. (C.) -60 (-51)
Viscosity, cP/-40 °F 10,900
Appearance Bright
Color Red

MEETS AND EXCEEDS OR SUITABLE FOR USE FOR THE FOLLOWING OEM automatic transmission specifications.

Aisin Warner AW-1, *Allison TES-295* and C-4, Audi G 052-025-A2, G 052-162-A1, BMW 7045E, LA2634, LT71141, Chrysler ATF's prior to 2006, Dexron®, Dexron® II, Dexron® III-D, Dexron® III-G, Dexron® III-H, Dexron® VI, Esso LT71141, Ford Mercon®, Ford Mercon LV, Ford Mercon SP, Ford Mercon® V, Ford 5NR5, Honda ATF-Z1, Hyundai SP-II, SP-III, Hyundai NWS-9638, Ide-mitsu K-17, JASO 1-A, JWS 3309, Kia SP-II, SP-III, MAN 339F, MAN 339 VI, 339 V2, 339 Z1, 339 Z2, Mazda ATF-M III, ATF-MV, Mercedes Benz 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11, Mitsubishi Diamond SP-II, SP-III, Nissan Matic-D, Matic J, Matic S, Shell 3403, LA2634, Subaru ATF, ATF-HP, Texaco ETL-7045E, ETL-8072B, N402, Toyota T-III, T-IV, WS (JWS 3324), Voith 55.6335.XX (G607), Voith 55.6336.XX (G1363), Volvo 97340, 97341, Volkswagon G-052-025-A2, G-052- 162-A1, ZF TE-ML 03D, TE-ML 04D, TE-ML 05L, TE-ML 09, TE-ML 11B, TE-ML 14A, TE-ML 14B, TE-ML 16L, TE-ML 17C.

DEXRON® is a registered trademark of General Motors Corp.

MERCON® is a registered trademark of Ford Motor Co.

Sharing lubricant knowledge and delivering the highest quality products, two things we promise our customers. The difference will change how you view, purchase and utilize greases and oils from here forward.

Family owned and operated since 1926.



842 N. Main St.

Fort Worth, TX 76164

(800) 332-1926

sales@royaloilus.com

www.royaloilus.com

