

# ROYAL OIL CO.

SPECIALTY LUBRICANTS

## POURABLE CRACK FILLER

**Extends the Life of Blacktop Surfaces**

**Quick & Easy to Use**

**Remains Pliable & Elastic**

**Seals Out Damaging Moisture**

**Environmentally Friendly**



### **APPLICATION**

*Contents may separate during shipping, therefore the jug must be shaken thoroughly before using. Cut spout to size and pour and force material into crack using a V-shaped squeegee. Although a surface skin begins to form within minutes after application do not open to traffic or coat with a Royal paving sealer for a minimum of 24 hours, depending on climate conditions. Cracks larger than 1 inch fill with a pourable slurry mix of a Royal Paving Sealer and a sand or Royal's Cold-flow Sealer.*

**Coverage:** For cracks measuring 1/2 inch wide and 1/2 inch deep, one gallon will approximately cover 80 linear feet.

POURABLE CRACK FILLER is chemically modified rubberized asphalt emulsion manufactured exclusively for the purpose of repairing small cracks in outside asphalt and concrete paving. It remains pliable and expands and contracts with temperature changes. It also helps seal out damaging moisture that can cause problems such as

# ***POURABLE CRACK FILLER***

## **Product Specifications**

Pourable Crack Filler is designed and recommended for use in unsealed cracks on asphalt and concrete parking lots and driveways.

Type:	Single component, chemically modified rubberized asphalt emulsion
Color:	Black (cured; Brown (uncured)
Solids:	66-70%
Density	9.0 pounds/gallon
Odor:	Bland
PH:	7-8
Brookfield Viscosity cP:	6000
Elongations %, ASTM D412	1000
Percent recovery	70
Flashpoint, Degrees °F	None to boiling point
Cure Time:	Approximately 24 hours, depending on climatic conditions
Crack Size: higher	For Cracks up to 1 inch (for cracks over 1/8 inch wide, fill to allow for slight shrinkage)
Minimum Application Temperature: within	40 °F (DO NOT apply when rain or frost is in the forecast 24 hours.)
Application:	Cold Applied– pour bucket or piston pump; V-shaped or U-shaped squeegee.
Clean-Up	Water (Liquid); Mineral spirits or kerosene (cured material)
Handling:	Store above 40 °F Reseal after use. (Always shake well before use)

Sharing lubricant knowledge and delivering the highest quality products, two things we promise our customers. The difference will change how you view, purchase and utilize greases and oils from here forward.

*Family owned and operated since 1926.*



842 N. Main St.  
Fort Worth, TX 76164  
(800) 332-1926  
sales@royaloilus.com  
www.royaloilus.com

